1200MM INDOOR/OUTDOOR UNDERMOUNT






SPECIFICATIONS

Rangehood TypeIndoor/Outdoor UndermountGTIN9351116002039Country of OriginHandcrafted in ItalyDesigned to Suit600-1200mm GAS or INDUCTIONControlsButton & RemoteSpeed Settings4Ducting Diameter200mm or 2x 150mmRecirculatingNoExtraction TypeOnboard MotorMotorTwin Aluminium MotorExtraction Rate2000m3/hrFilter Type25mm Stainless Steel BaffleNoise Level55dBa (min) to 67dBa (max)Lighting8 x 2.5W Led SpotlightsRun-on Timer10 MinsElectrical Requirement10AMax Current (W)420WProduct Dimensions (mm)W1200 x D540 x H335Cut-Out Dimensions (mm)W1160 x D505Weight42.5kgWarranty3 Years (6 years when Sirius ducting is used)		
Country of Origin Handcrafted in Italy Designed to Suit 600-1200mm GAS or INDUCTION Controls Button & Remote Speed Settings 4 Ducting Diameter 200mm or 2x 150mm Recirculating No Extraction Type Onboard Motor Motor Twin Aluminium Motor Extraction Rate 2000m3/hr Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Rangehood Type	Indoor/Outdoor Undermount
Designed to Suit 600-1200mm GAS or INDUCTION Controls Button & Remote Speed Settings 4 Ducting Diameter 200mm or 2x 150mm Recirculating No Extraction Type Onboard Motor Motor Twin Aluminium Motor Extraction Rate 2000m3/hr Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	GTIN	9351116002039
Controls Button & Remote Speed Settings 4 Ducting Diameter 200mm or 2x 150mm Recirculating No Extraction Type Onboard Motor Motor Twin Aluminium Motor Extraction Rate 2000m3/hr Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Country of Origin	Handcrafted in Italy
Speed Settings 4 Ducting Diameter 200mm or 2x 150mm Recirculating No Extraction Type Onboard Motor Motor Twin Aluminium Motor Extraction Rate 2000m3/hr Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Designed to Suit	600-1200mm GAS or INDUCTION
Ducting Diameter 200mm or 2x 150mm Recirculating No Extraction Type Onboard Motor Motor Twin Aluminium Motor Extraction Rate 2000m3/hr Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Controls	Button & Remote
Recirculating No Extraction Type Onboard Motor Motor Twin Aluminium Motor Extraction Rate 2000m3/hr Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Speed Settings	4
Extraction Type Onboard Motor Motor Twin Aluminium Motor Extraction Rate 2000m3/hr Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Ducting Diameter	200mm or 2x 150mm
Motor Twin Aluminium Motor Extraction Rate 2000m3/hr Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Recirculating	No
Extraction Rate 2000m3/hr Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Extraction Type	Onboard Motor
Filter Type 25mm Stainless Steel Baffle Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Motor	Twin Aluminium Motor
Noise Level 55dBa (min) to 67dBa (max) Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Extraction Rate	2000m3/hr
Lighting 8 x 2.5W Led Spotlights Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Filter Type	25mm Stainless Steel Baffle
Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Noise Level	55dBa (min) to 67dBa (max)
Electrical Requirement 10A	Lighting	8 x 2.5W Led Spotlights
Max Current (W) 420W Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Run-on Timer	10 Mins
Product Dimensions (mm) W1200 x D540 x H335 Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Electrical Requirement	10A
Cut-Out Dimensions (mm) W1160 x D505 Weight 42.5kg	Max Current (W)	420W
Weight 42.5kg	Product Dimensions (mm)	W1200 x D540 x H335
	Cut-Out Dimensions (mm)	W1160 x D505
Warranty 3 Years (6 years when Sirius ducting is used)	Weight	42.5kg
	Warranty	3 Years (6 years when Sirius ducting is used)

LINE DRAWING



KEY FEATURES



Twin Motor

Perfect for large and open kitchens, Sirius twin motor hoods boast powerful 2000M3/H extraction to efficiently remove steam, heat, smoke, and odours. With four speeds options for tailored ventilation.



25mm Stainless Steel Filters

Baffle filters feature interlocking baffles for effective grease removal, promoting smooth airflow. They're easy to maintain, offer superior filtration with a deep pleat design, and dishwasher safe.



Powerful Extraction

With a twin motor this rangehood's impressive maximum airflow of 2000M3/H, quickly and effectively removes smoke, steam, heat, odours, and other airborne particles from the kitchen.



Induction Safe

This rangehood boasts efficient filters and extraction capabilities to effectively manage increased steam and moisture levels resulting from minimal ambient heat compared to gas cooking methods.



8 x 2.5W Led Spotlights

This Sirius Rangehood takes it up a notch with eight powerful spotlights that provide efficient illumination while cooking.



Hand Crafted in Italy

Sirius Rangehoods, a prestigious Italian brand founded in 1996, is renowned for its bold designs and commitment to premium materials and craftsmanship, making it a top choice for high-end rangehoods.