
'THE LINE' 930MM CEILING CASSETTE






SPECIFICATIONS

Rangehood Type Ceiling Cassette GTIN 9351116003050 Country of Origin Handcrafted in Italy Designed to Suit 900mm GAS or INDUCTION Controls Remote Control Speed Settings 4 Ducting Diameter 150mm Recirculating No Extraction Type Offboard Motor Motor Options SEM 11, SEM 21, SEM 51 Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg Warranty 3 Years (6 years when Sirius ducting is used)		
Country of Origin Handcrafted in Italy Designed to Suit 900mm GAS or INDUCTION Controls Remote Control Speed Settings 4 Ducting Diameter 150mm Recirculating No Extraction Type Offboard Motor Motor Options SEM 11, SEM 21, SEM 51 Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight	Rangehood Type	Ceiling Cassette
Designed to Suit 900mm GAS or INDUCTION Controls Remote Control Speed Settings 4 Ducting Diameter 150mm Recirculating No Extraction Type Offboard Motor Motor Options SEM 11, SEM 21, SEM 51 Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	GTIN	9351116003050
Controls Remote Control Speed Settings 4 Ducting Diameter 150mm Recirculating No Extraction Type Offboard Motor Motor Options SEM 11, SEM 21, SEM 51 Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Country of Origin	Handcrafted in Italy
Speed Settings 4 Ducting Diameter 150mm Recirculating No Extraction Type Offboard Motor Motor Options SEM 11, SEM 21, SEM 51 Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Designed to Suit	900mm GAS or INDUCTION
Ducting Diameter 150mm Recirculating No Extraction Type Offboard Motor Motor Options SEM 11, SEM 21, SEM 51 Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Controls	Remote Control
Recirculating No Extraction Type Offboard Motor Motor Options SEM 11, SEM 21, SEM 51 Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Speed Settings	4
Extraction Type Offboard Motor Motor Options SEM 11, SEM 21, SEM 51 Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Ducting Diameter	150mm
Motor Options SEM 11, SEM 21, SEM 51 Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) Weight SEM 11, SEM 21, SEM 51 1200m3/hr Aluminium Filter Noise Level 1200m3/hr Aluminium Filter Depends on motor / installation 10 Mins Electrical Requirement 10 Mins Electrical Requirement 10 Max Current (W) 511W Product Dimensions (mm) Weight	Recirculating	No
Extraction Rate 1200m3/hr Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Extraction Type	Offboard Motor
Filter Type Aluminium Filter Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Motor Options	SEM 11, SEM 21, SEM 51
Noise Level Depends on motor / installation Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Extraction Rate	1200m3/hr
Lighting Dimmable And Dynamic Full Led 3W Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Filter Type	Aluminium Filter
Run-on Timer 10 Mins Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Noise Level	Depends on motor / installation
Electrical Requirement 10A Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Lighting	Dimmable And Dynamic Full Led 3W
Max Current (W) 511W Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Run-on Timer	10 Mins
Product Dimensions (mm) W930 x D440 x H200 Weight 32kg	Electrical Requirement	10A
Weight 32kg	Max Current (W)	511W
9	Product Dimensions (mm)	W930 x D440 x H200
Warranty 3 Years (6 years when Sirius ducting is used)	Weight	32kg
	Warranty	3 Years (6 years when Sirius ducting is used)

LINE DRAWING



KEY FEATURES



Offboard Green Energy Motor

Power, performance and quiet efficiency are the most important elements in the performance of your Sirus hood. Sirius has worked tirelessly to create a product that ticks all the boxes.



Aluminium Mesh Filter

Easy to install and maintain, but it also provides superior filtration capabilities. Designed with a special deep pleat design that helps capture cooking odours before they enter the room.



Powerful Extraction

Sirius offers powerful rangehoods, providing superior extraction for all cooking styles. With revolutionary technology and advanced engineering, they're ideal for any kitchen.



Induction Safe

This rangehood boasts efficient filters and extraction capabilities to effectively manage increased steam and moisture levels resulting from minimal ambient heat compared to gas cooking methods.



Dynamic Lighting

Sirius Rangehoods have a dynamic lighting system that can be adjusted from 2700 to 6500 kelvin to match other lighting in the room. Adjustable temperature, and dimmable. Maximum design flexibility.



Voice Control

Sirius introduces Voice Control, revolutionizing rangehood interaction. Users can command their hood using Google Assistant or Amazon Alexa, with intuitive responses.



Remote Control

This rangehood is equipped with a sophisticated, stylish remote control that offers users the convenience of adjusting fan speed, lighting and timer settings of the hood from a distance.



Hand Crafted In Italy

Sirius Rangehoods, a prestigious Italian brand founded in 1996, is renowned for its bold designs and commitment to premium materials and craftsmanship, making it a top choice for high-end rangehoods.