520mm OFFBOARD UNDERMOUNT RANGEHOOD

SL906EM-L 520





Rangehood type	Undermount
Control	Touch control
Speed settings	4
Ducting diameter	150mm
Extraction type	Offboard motor
Motor**	SEM 1, SEM 2 XS316, SEM 5 XS316
Extraction	1200m³/h
Filter	25mm stainless steel baffle
Lighting	6W LED strip
Induction Countdown Control	Yes
Electrical requirement	10A
Dimensions (mm)	W520 x D290 x H350
Cut-out dimensions (mm)	W501 x D265
Warranty	3 years (6 years when Sirius ducting is used)



350

265

*Product dimension includes trim

for ease of installation

Note: Need to allow 5mm extra



25mm BAFF FILTERS

100

501

520*

ø150



1200m³/h AIRFLOW








RMAN-MADE LED MOTOR LIGHTING



Ducting options



Eave or Wall ducted

- Can be used with SEM 1, SEM 2, and SEM 5.
- Use semi-rigid or rigid ducting, not fully flexible foil ducting.
- Fewer bends means a quieter and more powerful extraction.
- Extra 3 years warranty when Sirius ducting is used (total 6 years).
- See <u>support page</u> on Sirius website for installation videos and FAQs.

WARNING: technical specifications and product sizes can be varied by the manufacturer, without notice. Cut outs for appliances should only be by physical product measurements. The above information is indicative only.

Distributed by Arisit Pty Ltd

•

40-50 Mark Anthony Drive, Dandenong South VIC 3175

**Outdoor offboard motors have a marine grade finish as

standard for added resistance to coastal weather elements.

Ph: 1300 762 219

Fax: 03 9768 0838

06/2020

www.siriusbrand.com